

Dot laser, red, 650 nm, 2.5 mW

DB650-2.5-3-FA(14x45)
Order Number: 70100839

Main Parameters (*)	min	typ	max	Unit
Wavelength		650		nm
Optical Output Power		2.5		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	15	30	45	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty 1 years

Technical Parameters

Lifetime > 5,000 h
RoHS yes

Optical Parameters

Beam Shape Dot
Laser Class 3R
Divergence B - 0.3 mrad
Beam Diameter 5 mm
Size of Laserdot <4mm@5m
Operating Distance 50 m
Optics glass lens AR coated
Laser technology diode
Focus fixed (5.0m)

Electrical Parameters

Potential of Housing isolated
Power Supply Power Supply with stripped/tinned wires, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max.

Mechanical Parameters

Size Ø14x45 mm
Material Brass
Cable length 100 mm
Wire type 26AWG, 0,14mm²

Output Aperture	5 mm
Weight	35 g

(*) Over the complete operating temperature range

Features



- Laser Class 3R
- Operating Voltage 3V DC
- Glas lenses anti reflex coated
- Fixed focus
- Image processing

Picture



Cable color

Ground		black	GND
Positive		red	2.7 - 3.3, typ 3V DC

Safety Label



Valid Revision

3 | 11-JAN-2012