

Cross laser, red, 635 nm, 60°, 50 mW

CB635-50-3-F(20x73)60DEG
Order Number: 70135169

Main Parameters (*)	min	typ	max	Unit
Wavelength		635		nm
Optical Output Power		50		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	60	120	200	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Cross
Laser Class	2M
Divergence	B - 0.3 mrad
Fan Angle	60°
Operating Distance	10 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	adjustable
Verticality	< ± 0.5°

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max.

Mechanical Parameters

Size	Ø20x73 mm
Material	aluminium

Cable length	100 mm
Wire type	26AWG, 0,14mm²
Output Aperture	7 mm
Housing Color	black
Weight	54 g
Stripping of wire	5 mm

(*) Over the complete operating temperature range

Features



Picture



Cable color

Ground		black	GND
Positive		red	2.7 - 3.3, typ 3 V DC

Safety Label



Valid Revision

| 03-MAR-2021