



Cross laser, red, 650 nm, 5 °, 1 mW

CB650-1-5(20x90)5-ADJ-CON
Order Number: 70134667

Main Parameters (*)	min	typ	max	Unit
Wavelength	645	650	655	nm
Optical Diode Power	0.5	1	1	mW
Operating Voltage	4.5	5	5.5	V DC
Operating Current	5	20	40	mA
Operating Temperature	-10		40	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 10,000 h
RoHS	yes

Optical Parameters

Beam Shape	Cross
Laser Class	1M
Divergence	B - 0.3 mrad
Fan Angle	5 °
Operating Distance	5 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	adjustable

Electrical Parameters

Potential of Housing	isolated
Connector	2.5 mm DC socket (+ pole inner)
Power Supply	LFNT-5

Mechanical Parameters

Size	Ø20x90 mm
Material	aluminium

Wire type	24AWG, black, 3mm
Output Aperture	6 mm
Housing Color	black
Weight	72 g

(*) Over the complete operating temperature range

Features

- Operating Voltage 5V DC
- Laser Class 1M
- Low cost
- Fan angle 5 °
- Compact size


Picture



Cable color

Ground		black	GND
Positive		red	4.5 - 5.5, typ 5 V DC

Safety Label



Valid Revision

| 11-DEC-2023