

## Dot laser, green, 532 nm, 15 mW

DA532-15-3(20x95)  
Order Number: 70100372

Main Parameters (*)	min	typ	max	Unit
Wavelength		532		nm
Optical Output Power		15		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	180	350	450	mA
Operating Temperature	15		30	°C
Storage Temperature	-40		80	°C

### Main Data

Warranty	1 years
----------	---------

### Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

### Optical Parameters

Beam Shape	Dot
Laser Class	3B
Divergence	A - 0.1 mrad
Beam Diameter	8 mm
Size of Laserdot	<4mm@10m
Operating Distance	350 m
Optics	glass lens AR coated
Beam Mode	TEM00
Laser technology	YVO4+KTP
Stability	+/- 20% @ 15-30°C
Focus	collimated
Warm up time	< 15 min

### Electrical Parameters

Potential of Housing	isolated
----------------------	----------

### Mechanical Parameters

Size	Ø20x95 mm
------	-----------

Material	aluminium
Cable length	100 mm
Output Aperture	8 mm
Housing Color	black
Weight	74 g

(\*) Over the complete operating temperature range

### Features



### Picture



### Cable color

Ground		blue	GND
Positive		red	2.7 - 3.3, typ 3 V DC

### Safety Label



### Valid Revision

3 | 23-NOV-2017