

Dot laser, green, 532 nm, 12 mW

DB532-12-3-FA(22x105)-S-AP
Order Number: 70135404

Main Parameters (*)	min	typ	max	Unit
Wavelength		532		nm
Optical Output Power		12		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	150	200	300	mA
Operating Temperature	15		30	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Dot
Laser Class	3R
Divergence	B - 0.3 mrad
Beam Diameter	3 mm
Size of Laserdot	<3.5mm@5m
Operating Distance	10 m
Optics	glass lens AR coated
Beam Mode	TEM00
Laser technology	Solid State (YVO4+KTP)
Axial Divergence	± 0.25 °
Focus	fixed (5.0m)
Warm up time	< 15 min

Electrical Parameters

Potential of Housing	VDD(+)
Battery	CR123A Lithium Battery, 3V 1400mAh

Battery count	1
---------------	---

Mechanical Parameters

Size	Ø22x105 mm
Material	aluminium
Output Aperture	3.5 mm
Housing Color	black
Weight	74 g

(*) Over the complete operating temperature range

Features



- Axial parallel
- With battery
- Glas lenses anti reflex coated
- Compact size
- Laser Class 3R

Picture



Safety Label



Valid Revision

| 26-SEP-2019