

Dot laser, red, 670 nm, 1 mW

DB670-1-3-FA(14x45)
Order Number: 70100457

Main Parameters (*)	min	typ	max	Unit
Wavelength		670		nm
Optical Output Power		1		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	25	45	70	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Dot
Laser Class	2
Divergence	B - 0.3 mrad
Beam Diameter	5 mm
Size of Laserdot	<4mm@5m
Operating Distance	50 m
Optics	glass lens AR coated
Laser technology	diode
Focus	fixed (5.0m)

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max.

Mechanical Parameters

Size	Ø14x45 mm
------	-----------

Material	Brass
Cable length	100 mm
Wire type	26AWG, 0,14mm ²
Output Aperture	5 mm
Weight	35 g

(*) Over the complete operating temperature range

Features



- Operating Voltage 3V DC
- Glas lenses anti reflex coated
- Compact size
- Fixed focus
- Laser Class 2

Picture



Cable color

Ground		black	GND
Positive		red	2.7 - 3.3, typ 3 V DC

Safety Label



Valid Revision

5 | 22-JUL-2020