

Dot laser, red, 650 nm, 1 mW

DBI650-1-24-FA(12X60)-F3400-CON
Order Number: 70156492

Main Parameters (*)	min	typ	max	Unit
Wavelength		650		nm
Optical Output Power		1		mW
Operating Voltage	23.5	24	25.5	V DC
Operating Current	1	5	15	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Dot
Laser Class	2
Divergence	B - 0.3 mrad
Size of Laserdot	<1.25mm@3.4m
Operating Distance	3.4 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	fixed (3.4m)

Electrical Parameters

Potential of Housing	isolated
Connector	CON-M8-3POL
Power Supply	Power Supply, Output: 24V DC, Input: 100-240V AC, 50-60Hz, Output Power: 24W max., incl. Connector M8

Mechanical Parameters

Size	Ø12x60 mm
Material	aluminium

Cable length	500 mm
Wire type	22AWG, black, 3,6mm
Output Aperture	5 mm
Housing Color	black
Weight	10.5 g

(*) Over the complete operating temperature range

Features



- Operating Voltage 24 V DC
- Isolated housing
- Laser Class 2
- Fixed focus
- Compact size

Picture



Cable color

Positive		red	23.5 - 25.5, typ 24 V DC
Ground		black	GND

Safety Label



Valid Revision

| 07-AUG-2025