

Doe laser, blue, 450 nm, 15 mW

DD450-15-24(20x135)-M12-DOE
Order Number: 70148633

Main Parameters (*)	min	typ	max	Unit
Wavelength	445	450	455	nm
Optical Output Power	13	15	20	mW
Operating Voltage	21.6	24	26.4	V DC
Operating Current	15	75	115	mA
Operating Temperature	-10		60	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 10,000 h
RoHS	yes

Optical Parameters

Beam Shape	DOE
Laser Class	3B
Divergence	D - 0.5 mrad
Line Thickness	adjustable
Operating Distance	10 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Stability	+/- 3% @ -10-50°C
Protection Lens	yes
Focus	adjustable

Electrical Parameters

Potential of Housing	isolated
ESD Protection	IEC 61000-4-2
Connector	CON-M12

Power Supply	Power Supply, Output: 24V DC, Input: 100-240V AC, 50-60Hz, Output Power: 24W max. SYS 1308-2424-W2E 2,1 x 5,5 x 11 center positive
--------------	--

Mechanical Parameters

Size	Ø20x135 mm
Material	Stainless Steel
Output Aperture	16 mm
Housing Color	blue
Weight	350 g

Protection Class	IP64
------------------	------

(*) Over the complete operating temperature range

Features




- Stainless steel for industrial applications
- Protection Class (IP64)
- Adjustable focus
- M12 industrial connector
- Protection lens

Picture



Drawing



Safety Label



Valid Revision

| 31-AUG-2023