

Doe laser, green, 532 nm, 30 mW

DD532-30-230(40x210)-DOE
Order Number: 70115307

Main Parameters (*)	min	typ	max	Unit
Wavelength		532		nm
Optical Output Power		30		mW
Operating Voltage	207	230	253	V AC
Operating Current	5	10	15	mA
Operating Temperature	15		30	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 10,000 h
RoHS	yes

Optical Parameters

Beam Shape	DOE
Laser Class	3B
Divergence	D - 0.5 mrad
Operating Distance	100 m
Optics	glass lens AR coated
Beam Mode	TEM00
Laser technology	YVO4+KTP
Stability	+/- 20% @ 15-30°C
Focus	adjustable
Warm up time	< 15 min

Electrical Parameters

Potential of Housing	isolated
Connector	AC CEE 7/7

Mechanical Parameters

Size	Ø40x210 mm
Material	aluminium
Cable length	1,700 mm
Wire type	H05VV-F
Output Aperture	5 mm
Weight	600 g

(*) Over the complete operating temperature range

Features




- DOE Laser
- Glas lenses anti reflex coated
- With 230V power supply
- High power
- Adjustable focus

Picture



Drawing



Safety Label



Valid Revision

1 | 19-MAR-2019