

## Doe laser, red, 635nm, 0.4mW

DD635-0.4-3(12x38)-DOE

Order Number: 70114720

Main Parameters (*)	min	typ	max	Unit
Wavelength		635		nm
Optical Output Power		0.4		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	15	24	45	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

### Technical Parameters

Lifetime	>5000h
RoHS	yes

### Optical Parameters

Beam Shape	DOE
Laser Class	1
Divergence	D - 0.5mrad
Operating Distance	5m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	adjustable

### Electrical Parameters

Potential of Housing	isolated
Power Supply	LFNT-3

### Mechanical Parameters

Size	Ø12x38mm
Material	aluminium
Cable length	100mm
Wire type	Belden, Typ 1007, 26AWG
Output Aperture	5mm
Housing Color	black
Weight	9.5g
Stripping of wire	5mm

(\*) Over the complete operating temperature range

### Features



- Adjustable focus
- DOE optic can be changed
- Compact size
- Glas lenses anti reflex coated
- Operating Voltage 3V DC


### Picture




### Cable Colors

Ground		black	GND
Positive		red	2.7 - 3.3, typ 3V DC

### Drawing



### Safety Label



### Revision

REV 1 | 14-JAN-2016