

Doe laser, red, 635 nm, 5 mW

DD635-5-24(16x65)-DOE283
Order Number: 70143393

Main Parameters (*)	min	typ	max	Unit
Wavelength		635		nm
Optical Output Power		5		mW
Operating Voltage	23.5	24	24.5	V DC
Operating Current	5	12	30	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty 1 years

Technical Parameters

Lifetime > 10,000 h
RoHS yes

Optical Parameters

Beam Shape	DOE
Laser Class	2M
Divergence	D - 0.5 mrad
Operating Distance	3m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Stability	+/- 3% @ -10-50°C
Focus	adjustable

Electrical Parameters

Potential of Housing	isolated
Stripping of cable cover	50 mm

Mechanical Parameters

Size	Ø16x65 mm
Material	aluminium
Cable length	300 mm
Wire type	18AWG, black, 3,6mm

Output Aperture	5 mm
Housing Color	black
Weight	30g
Stripping of wire	5 mm

(*) Over the complete operating temperature range

Features





- Adjustable focus
- DOE optic can be changed
- Compact size
- Glas lenses anti reflex coated
- Operating Voltage 24 V DC

Picture



Cable color

Ground		black	GND
Positive		white	23.5 - 24.5, typ 24 V DC

Safety Label



Valid Revision

| 26-JUN-2020