

Dot laser, red, 655 nm, 0.38 mW

DD650-0.43-4(14X30)-AP
Order Number: 70125009

Main Parameters (*)	min	typ	max	Unit
Wavelength	645	655	660	nm
Optical Output Power	0.35	0.38	0.43	mW
Operating Voltage	3.5	4	4.5	V DC
Operating Current		10		mA
Operating Temperature	-10		50	°C
Storage Temperature	-40		60	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 50,000 h
RoHS	yes

Optical Parameters

Beam Shape	Dot
Laser Class	2
Divergence	D - 0.5 mrad
Beam Diameter	3 mm
Operating Distance	10 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Opt. Power Stability at const. Temp.	< 1 %
Stability	< 8% @ -10 - 50°C
Axial Divergence	± 2°
Focus	collimated
Pointing Stability	< 0.2°
Tolerances for light polarisation	± 5°

Electrical Parameters

Rise Time	< 100 ms
Potential of Housing	isolated
ESD Protection	IEC 61000-4-2

Mechanical Parameters

Size	Ø14x30 mm
Material	aluminium
Cable length	150 mm
Wire type	Belden, Typ 1095, 28AWG
Output Aperture	3 mm
Housing Color	black
Weight	11.3 g

(*) Over the complete operating temperature range

Features



- Operating Voltage 4 V DC
- Laser Class 2
- Image processing
- Glas lenses anti reflex coated
- Uniform illumination

Picture



Cable color

Ground		blue	GND
Positive		red	3.5 - 4.5, typ 4 V DC

Safety Label



Valid Revision

| 10-DEC-2019