

Dot laser, red, 635 nm, 6 mW

DE635-6-3(12x34)
Order Number: 70101782

Main Parameters (*)	min	typ	max	Unit
Wavelength		635		nm
Optical Output Power		6		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	30	60	90	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Dot
Laser Class	3B
Divergence	E - 0.6 mrad
Size of Laserdot	adjustable
Operating Distance	60 m
Optics	glass lens AR coated
Laser technology	diode
Focus	adjustable

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max.

Mechanical Parameters

Size	Ø12x34 mm
Material	Brass
Cable length	100 mm
Wire type	26AWG, 0,14mm ²
Output Aperture	5 mm
Weight	16 g

(*) Over the complete operating temperature range

Features



- Operating Voltage 3V DC
- Adjustable focus
- Glas lenses anti reflex coated
- Laser Class 3B
- Compact size


Picture



Cable color

Ground		black	GND
Positive		red	2.7 - 3.3, typ 3 V DC

Drawing



Safety Label



Valid Revision

1 | 07-MAY-2011