

Dot laser, red, 650 nm, 24 mW

DH650-24-3(14x45)
Order Number: 70102192

Main Parameters (*)	min	typ	max	Unit
Wavelength		650		nm
Optical Output Power		24		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	60	80	180	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Dot
Laser Class	3B
Divergence	H - 1.0 mrad
Size of Laserdot	adjustable
Operating Distance	100 m
Optics	glass lens AR coated
Laser technology	diode
Focus	adjustable

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max.

Mechanical Parameters

Size	Ø14x45 mm
Material	aluminium
Cable length	100 mm
Wire type	26AWG, 0,14mm ²
Output Aperture	5 mm
Weight	16.5 g

(*) Over the complete operating temperature range

Features



- Compact size
- Adjustable focus
- Operating Voltage 3V DC
- Laser Class 3B
- High Power


Picture



Cable color

Ground		black	GND
Positive		red	2.7 - 3.3, typ 3 V DC

Drawing



Safety Label



Valid Revision

8 | 09-DEC-2011