

Dot laser, red, 650 nm, 0.4 mW

DI650-0.4-5(8x21)-ADJ
Order Number: 70130942

Main Parameters (*)	min	typ	max	Unit
Wavelength		650		nm
Optical Output Power		0.4		mW
Operating Voltage	4.7	5	5.3	V DC
Operating Current	10	18	40	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Dot
Laser Class	1
Divergence	1 - 1.5 mrad
Size of Laserdot	adjustable
Operating Distance	10 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	adjustable

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 5V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3W max.

Mechanical Parameters

Size	Ø8x21 mm
Material	aluminium
Cable length	150 mm
Wire type	AFR200, 0.1mm ² , 0.78mm
Output Aperture	2 mm
Housing Color	black
Weight	3 g
Stripping of wire	5 mm

(*) Over the complete operating temperature range

Features



- Operating Voltage 5 V DC
- Laser Class 1
- Image processing
- Adjustable focus
- Compact size


Picture



Cable color

Ground		blue	GND
Positive		red	4.7 - 5.3, typ 5 V DC

Drawing



Safety Label



Valid Revision

| 25-MAR-2021