

Dot laser, red, 635 nm, 0.7 mW

DN635-0.7-5(10.6x12.2)-F200
Order Number: 70140897

Main Parameters (*)	min	typ	max	Unit
Wavelength		635		nm
Optical Output Power	0.5	0.7	0.9	mW
Operating Voltage	3	5	6	V DC
Operating Current	10	30	40	mA
Operating Temperature	-10		50	°C
Storage Temperature	-20		60	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 10,000 h
RoHS	yes

Optical Parameters

Beam Shape	Dot
Laser Class	2
Divergence	N - 4.0 mrad
Size of Laserdot	0.13x0.05mm@0.2m
Operating Distance	0.2m
Optics	acryl lense
Laser technology	diode
Focus	fixed (200mm)

Electrical Parameters

Potential of Housing	VDD(+)
Power Supply	Power Supply with stripped/tinned wires, Output: 5V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3W max.

Mechanical Parameters

Size	Ø10.6x12.2 mm
Material	Brass
Cable length	115 mm

Wire type	26AWG, UL, isolated
Output Aperture	5 mm
Housing Color	brass
Weight	5g
Stripping of wire	3 mm

(*) Over the complete operating temperature range

Features



- Compact size
- Laser Class 2
- Low power consumption
- Operating Voltage 3-6V DC

Picture



Cable color

Ground		black	GND
Positive		red	3 - 6, typ 5 V DC

Safety Label



Valid Revision

| 09-MAR-2021