

Doe laser, green, 532 nm, 15 mW

DOE212-532-15-24(20X135)-M12
Order Number: 70156300

Main Parameters (*)	min	typ	max	Unit
Wavelength	525	532	537	nm
Optical Output Power	12	15	17	mW
Operating Voltage	21.6	24	26.4	V DC
Operating Current	40	75	115	mA
Operating Temperature	15		30	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 10,000 h
RoHS	yes

Optical Parameters

Beam Shape	DOE
Laser Class	2M
Divergence	D - 0.5 mrad
Operating Distance	15 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Stability	+/- 10% @ 15-30°C
Protection Lens	yes
Focus	adjustable
Warm up time	< 15 min

Electrical Parameters

Potential of Housing	isolated
ESD Protection	IEC 61000-4-2
Connector	CON-M12

Power Supply	Power Supply, Output: 24V DC, Input: 100-240V AC, 50-60Hz, Output Power: 24W max. SYS 1308-2424-W2E 2,1 x 5,5 x 11 center positive
--------------	--

Mechanical Parameters

Size	Ø20x135 mm
Material	Stainless Steel
Output Aperture	16 mm
Housing Color	green
Weight	350 g
Protection Class	IP 64

DOE

Alpha	25°
-------	-----

(*) Over the complete operating temperature range

Features




- Stainless steel body for industrial applications
- Protection Class (IP64)
- Adjustable focus
- M12 industrial connector
- Protection lens


Picture



Drawing



Safety Label



Valid Revision

| 01-SEP-2023