

## Doe laser, green, 532 nm, 5 mW

DOE218-532-5-3(16x90)-NT  
Order Number: 70110944

Main Parameters (*)	min	typ	max	Unit
Wavelength		532		nm
Optical Output Power		5		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	125	250	375	mA
Operating Temperature		15	30	°C
Storage Temperature	-40		80	°C

### Main Data

Warranty 1 years

### Technical Parameters

Lifetime > 5,000 h  
RoHS yes

### Optical Parameters

Beam Shape DOE  
Laser Class 2M  
Divergence D - 0.5 mrad  
Optics acryl lens  
Laser technology Solid State (YVO4+KTP)  
Stability +/- 20% @ 15-30°C  
Protection Lens yes  
Focus fixed  
Warm up time < 15 min

### Electrical Parameters

Potential of Housing VDD(+)  
Connector 2.5 mm DC plug (GND pole inner)  
Power Supply Power Supply, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max, Connector 2,5x5,5x9,5mm center negative

### Mechanical Parameters

Size Ø16x90 mm

Material	aluminium
Cable length	1,360 mm
Output Aperture	6 mm
Housing Color	cyan
Weight	43 g

### DOE

Alpha	15°
a	26 mm
Diameter (without holder)	8 mm
Width (without Holder)	1 mm
Material	PMMA

(\*) Over the complete operating temperature range

### Features



- DOE Laser
- Image processing
- Laser Class 2M
- Compact size

### Picture



### Safety Label



### Valid Revision

1 | 14-APR-2020