

## DOE laser, green, 532 nm, 25 °, 5 mW

DOE247-532-5-3(16x90)-NT  
Order Number: 70111057

Main Parameters (*)	min	typ	max	Unit
Wavelength		532		nm
Optical Output Power		5		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	125	250	375	mA
Operating Temperature	15		30	°C
Storage Temperature	-40		80	°C

### Main Data

Warranty 1 Jahre

### Technical Parameters

Lifetime > 5,000 h  
RoHS yes

### Optical Parameters

Beam Shape	DOE
Laser Class	2
Divergence	D - 0.5 mrad
Fan Angle	25 °
Optics	acryl lense
Laser technology	Solid State (YVO4+KTP)
Stability	+/- 20% @ 15-30°C
Protection Lens	yes
Focus	fixed
Warm up time	< 15 min

### Electrical Parameters

Potential of Housing	VDD(+)
Connector	2.5 mm DC plug (GND pole inner)
Power Supply	LFNT-3-C

### Mechanical Parameters

Size	Ø16x90 mm
Material	aluminium
Cable length	1,360 mm
Output Aperture	6 mm
Housing Color	cyan
Weight	43 g

### DOE

Alpha	25 °
a	44 mm
Diameter (without holder)	8 mm
Width (without Holder)	1.2 mm
Material	PC

(\*) Over the complete operating temperature range

### Features




- DOE Laser
- Image processing
- Laser Class 2
- Compact size

### Picture



### Safety Label



### Valid Revision

1 | 03-JAN-2018