

Doe laser, red, 635 nm, 5 mW

DOE254-635-5-6(10x24)
Order Number: 70132410

Main Parameters (*)	min	typ	max	Unit
Wavelength		635		nm
Optical Diode Power		5		mW
Operating Voltage	3	5	6	V DC
Operating Current	25	45	65	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Stammdaten

Warranty	1 Jahre
----------	---------

Technical Parameters

Lifetime	>3000 h
RoHS	yes

Optical Parameters

Beam Shape	DOE
Laser Class	2M
Divergence	H - 1.0 mrad
Optics	acryl lense
Laser technology	diode
Protection Lens	yes
Focus	adjustable

Electrical Parameters

Potential of Housing	VDD(+)
----------------------	--------

Mechanical Parameters

Size	Ø10x24 mm
Material	Brass
Cable length	100 mm
Wire type	26AWG, 0,14mm²
Output Aperture	6 mm
Weight	8.5 g

DOE

Alpha	37 °
Beta	27 °
Gamma	1.12 °
Delta	27 °
a	68 mm
b	48 mm
c	2 mm
d	48 mm
Diameter (without holder)	8 mm
Width (without Holder)	1.2 mm
Material	PC

(*) Over the complete operating temperature range

Features




Picture



Cable color

Ground		black	GND
positive		red	3 - 6, typ 5 V DC

safety label



Valid Revision

| 29-JUL-2020