

Doe laser, green, 532 nm, 5 mW

DOE257-532-5-3(16x90)-NT
Order Number: 70111156

Main Parameters (*)	min	typ	max	Unit
Wavelength		532		nm
Optical Output Power		5		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	125	250	375	mA
Operating Temperature		15	30	°C
Storage Temperature		-40	80	°C

Main Data

Warranty 1 years

Technical Parameters

Lifetime > 5,000 h
RoHS yes

Optical Parameters

Beam Shape	DOE
Laser Class	2M
Divergence	D - 0.5 mrad
Optics	acryl lense
Laser technology	Solid State (YVO4+KTP)
Stability	+/- 20% @ 15-30°C
Protection Lens	yes
Focus	fixed
Warm up time	< 15 min

Electrical Parameters

Potential of Housing	VDD(+)
Connector	2.5 mm DC plug (GND pole inner)
Power Supply	Power Supply, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max, Connector 2,5x5,5x9,5mm center negative

Mechanical Parameters

Size	Ø16x90 mm
Material	aluminium
Cable length	1,360 mm
Output Aperture	6 mm

Housing Color	cyan
Weight	43g

DOE

Alpha	31.5°
Beta	22.5°
Gamma	0.45°
Delta	22.5°
a	56.4 mm
b	40 mm
c	0.8 mm
d	40 mm
Diameter (without holder)	8 mm
Width (without Holder)	1.2 mm
Material	PC

(*) Over the complete operating temperature range

Features



- DOE Laser
- Image processing
- Laser Class 2M
- Compact size

Picture



Safety Label



Valid Revision

1 | 27-AUG-2019