

Doe laser, red, 635 nm, 5 mW

DOE258-635-5-3(16x90)-NT
Order Number: 70111521

Main Parameters (*)	min	typ	max	Unit
Wavelength		635		nm
Optical Output Power		5		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	30	60	90	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty 1 years

Technical Parameters

Lifetime > 5,000 h
RoHS yes

Optical Parameters

Beam Shape DOE
Laser Class 2M
Optics glass lens AR coated
Laser technology diode
Protection Lens yes
Focus fixed

Electrical Parameters

Potential of Housing VDD(+)
Connector 2.5 mm DC plug (GND pole inner)
Power Supply Power Supply, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max, Connector 2,5x5,5x9,5mm center negative

Mechanical Parameters

Size Ø16x90 mm
Material aluminium
Cable length 1,360 mm
Output Aperture 6 mm
Housing Color cyan
Weight 43 g

DOE

Alpha	38.8°
Beta	28°
Gamma	2.8°
Delta	28°
a	70.4 mm
b	49.8 mm
c	4.98 mm
d	49.8 mm
Diameter (without holder)	8 mm
Width (without Holder)	1.2 mm
Material	PC

(*) Over the complete operating temperature range

Features



- DOE Laser
- Image processing
- With 230V power supply
- Glas lenses anti reflex coated
- Fixed focus

Picture



Safety Label



Valid Revision

1 | 13-FEB-2020