

Doe laser, blue, 450 nm, 40 mW

DOE281-DD450-40-3(16x65)
Order Number: 70146912

Main Parameters (*)	min	typ	max	Unit
Wavelength		450		nm
Optical Output Power	35	40	45	mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	5	15	30	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 10,000 h
RoHS	yes

Optical Parameters

Beam Shape	DOE
Laser Class	3R
Divergence	D - 0.5 mrad
Operating Distance	10 m
Optics	glass lens AR coated
Laser technology	diode
Focus	adjustable

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max.
Stripping of cable cover	20 mm

Mechanical Parameters

Size	Ø16x65 mm
Material	aluminium

Cable length	130 mm
Wire type	18AWG, black, 3,6mm
Output Aperture	5 mm
Weight	9.5g
Stripping of wire	10 mm

(*) Over the complete operating temperature range

Features



- Adjustable focus
- DOE optic can be changed
- Compact size
- Glas lenses anti reflex coated
- Operating Voltage 3V DC

Picture



Cable color

Ground		black	GND
Positive		red	2.7 - 3.3, typ 3 V DC

Safety Label



Valid Revision

| 07-MAY-2020