

DOE laser, red, 635 nm, 5 mW

DOE286-635-5-3(16x90)-NT
Order Number: 70118995

Main Parameters (*)	min	typ	max	Unit
Wavelength		635		nm
Optical Output Power		5		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	30	60	90	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty 1 years

Technical Parameters

Lifetime > 5,000 h
RoHS yes

Optical Parameters

Beam Shape DOE
Laser Class 2M
Divergence D - 0.5 mrad
Operating Distance 1 m
Optics glass lens AR coated
Laser technology diode
Protection Lens yes
Focus fixed

Electrical Parameters

Potential of Housing VDD(+)
Connector 2.5 mm DC plug (GND pole inner)

Power Supply Power Supply, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max, Connector 2,5x5,5x9,5mm center negative

Mechanical Parameters

Size Ø16x90 mm

Material	aluminium
Cable length	1,360 mm
Output Aperture	6 mm
Housing Color	cyan
Weight	43 g

DOE

Alpha 29°
a 52 mm
Diameter (without holder) 8 mm
Width (without Holder) 1.2 mm
Material PC

(*) Over the complete operating temperature range

Features



- DOE Laser
- Image processing
- With 230V power supply
- Glas lenses anti reflex coated
- Fixed focus

Picture



Safety Label



Valid Revision