

Expander Laser, green, 532 nm, 5 mW

E532-5-5(24x120)APT20
Order Number: 70120431

Main Parameters (*)	min	typ	max	Unit
Wavelength		532		nm
Optical Output Power		5		mW
Operating Voltage	4.7	5	5.3	V DC
Operating Current	80	100	180	mA
Operating Temperature	15		30	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	expander
Laser Class	2M
Operating Distance	150 m
Optics	glass lens AR coated
Beam Mode	TEM00
Laser technology	Solid State (YVO4+KTP)
Stability	+/- 20% @ 15-30°C
Focus	adjustable
Warm up time	< 15 min

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 5V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3W max.

Mechanical Parameters

Size	Ø24x120 mm
Material	aluminium
Cable length	100 mm

Wire type	26AWG, 0,14mm²
Output Aperture	20 mm
Housing Color	black
Weight	120 g
Stripping of wire	5 mm

(*) Over the complete operating temperature range

Features



- Operating Voltage 5V DC
- Glas lenses anti reflex coated
- Laser Class 2M
- Adjustable focus
- Uniform illumination

Picture



Cable color

Ground		black	GND
Positive		red	4.7 - 5.3, typ 5 V DC

Safety Label



Valid Revision

| 25-MAY-2020