

Line laser, red, 650 nm, 30°, 16 mW

LC650-16-3(14x55)30-F78-C120
Order Number: 70148343

Main Parameters (*)	min	typ	max	Unit
Wavelength		650		nm
Optical Output Power		16		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	40	64	100	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Line
Laser Class	2M
Divergence	C - 0.4 mrad
Fan Angle	30°
Operating Distance	0.078 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	fixed

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max.

Mechanical Parameters

Size	Ø14x55 mm
Material	aluminium
Cable length	120 mm

Wire type	Belden, Typ 1007, 26AWG
Output Aperture	3.5 mm
Housing Color	black
Weight	16.5 g
Stripping of wire	5 mm

(*) Over the complete operating temperature range

Features



- Operating Voltage 3 V DC
- Small fan angle
- Image processing

Picture



Cable color

Ground		black	GND
Positive		red	2.7 - 3.3, typ 3 V DC

Safety Label



Valid Revision

| 06-AUG-2020