



Dot laser, green, 532 nm, 5 mW

LFD532-5-3(12x60)-C35
Order Number: 70151428

Main Parameters (*)	min	typ	max	Unit
Wavelength		532		nm
Optical Output Power		5		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	125	250	375	mA
Operating Temperature	15		30	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Dot
Laser Class	3R
Divergence	D - 0.5 mrad
Beam Diameter	3 mm
Size of Laserdot	<5mm@10m
Operating Distance	150 m
Optics	glass lens AR coated
Beam Mode	TEM00
Laser technology	YVO4+KTP
Stability	+/- 20% @ 15-30°C
Focus	collimated
Warm up time	< 15 min

Electrical Parameters

Potential of Housing	isolated
----------------------	----------

Power Supply	Power Supply with stripped/tinned wires, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max.
--------------	--

Mechanical Parameters

Size	Ø12x60 mm
Material	aluminium
Cable length	35 mm
Output Aperture	3 mm
Weight	13 g

(*) Over the complete operating temperature range

Features



- Operating Voltage 3V DC
- Isolated housing
- Laser Class 3R
- Compact size
- Fixed focus


Picture



Cable color

Ground		blue	GND
Positive		red	2.7 - 3.3, typ 3 V DC

Drawing



Safety Label



Valid Revision

| 20-AUG-2024