

Line laser, green, 532 nm, 90°, 30 mW

Output Power: 24W max.
SYS 1308-2424-W2E | 2,1 x 5,5
x 11 center positive

LH532-30-24(20x120)-M12-BR
Order Number: 70130683

Main Parameters (*)	min	typ	max	Unit
Wavelength		532		nm
Optical Output Power		30		mW
Operating Voltage	21.6	24	26.4	V DC
Operating Current	100	150	250	mA
Operating Temperature	15		30	°C
Storage Temperature	-40		80	°C

Main Data

Warranty 1 years

Technical Parameters

Lifetime >6,000 h
RoHS yes

Optical Parameters

Beam Shape	Line
Laser Class	2M
Divergence	H - 1.0 mrad
Fan Angle	90°
Line Thickness	<1.5mm@2m
Operating Distance	2 m
Optics	glass lens AR coated
Beam Mode	TEM00
Laser technology	Solid State (YVO4+KTP)
Stability	+/- 10% @ 15-30°C
Protection Lens	yes
Focus	fixed (2000mm)
Warm up time	< 15 min

Electrical Parameters

Potential of Housing	isolated
Connector	CON-M12
Power Supply	Power Supply, Output: 24V DC, Input: 100-240V AC, 50-60Hz,

Mechanical Parameters

Size	Ø20x120 mm
Material	aluminium
Output Aperture	5.5 mm
Housing Color	black
Weight	80 g
Protection Class	IP 64


(*) Over the complete operating temperature range

Features



- Operating Voltage 24V DC
- Isolated housing
- Laser Class 2M
- Protection lens
- M12 Connector

Picture



Safety Label



Valid Revision

| 12-SEP-2023