

Line laser, red, 635 nm, 30°, 7 mW

LH635-7-5(12x32)30DEG-F100
Order Number: 70110739

Main Parameters (*)	min	typ	max	Unit
Wavelength		635		nm
Optical Output Power		7		mW
Operating Voltage	4.5	5	5.5	V DC
Operating Current	30	60	90	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 10,000 h
RoHS	yes

Optical Parameters

Beam Shape	Line
Laser Class	2
Divergence	H - 1.0 mrad
Fan Angle	30°
Line Thickness	<0.3mm@0.1m
Operating Distance	0.1 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	fixed (100mm)

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 5V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3W max.

Mechanical Parameters

Size	Ø12x32 mm
Material	aluminium
Cable length	100 mm
Wire type	26AWG, 0,14mm ²
Output Aperture	5.5 mm
Housing Color	black
Weight	14 g
Stripping of wire	5 mm

(*) Over the complete operating temperature range

Features



- Image processing
- Uniform line thickness
- Laser Class 2
- Compact size


Picture



Cable color

Ground		black	GND
Positive		red	4.5 - 5.5, typ 5 V DC

Drawing



Safety Label



Valid Revision

9 | 22-APR-2021