

Line laser, red, 650 nm, 90°, 16 mW

LH650-16-24(20x80)-PL-C3000
Order Number: 70109849

Main Parameters (*)	min	typ	max	Unit
Wavelength		650		nm
Optical Output Power		16		mW
Operating Voltage	21.6	24	26.4	V DC
Operating Current	3	11	30	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 10,000 h
RoHS	yes

Optical Parameters

Beam Shape	Line
Laser Class	2
Divergence	H - 1.0 mrad
Fan Angle	90°
Line Thickness	<1.5mm@3m
Operating Distance	5m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Protection Lens	yes
Focus	fixed (3000mm)

Electrical Parameters

Potential of Housing	isolated
Stripping of cable cover	50 mm

Mechanical Parameters

Size	Ø20x80 mm
Material	aluminium
Cable length	3,000 mm
Wire type	22AWG, black, 3,6mm

Output Aperture	5.5 mm
Housing Color	black
Weight	98 g
Protection Class	IP54
Stripping of wire	5 mm

(*) Over the complete operating temperature range

Features




- Operating Voltage 24 V DC
- Laser Class 2
- Uniform line thickness
- High Power
- Small laser head

Picture



Cable color

Ground		black	GND
Positive		white	21.6 - 26.4, typ 24 V DC

Safety Label



Valid Revision

13 | 14-NOV-2024