

Line laser, red, 650 nm, 90°, 16 mW

LH650-16-24(20x80)-PL-F300
Order Number: 70132298

Main Parameters (*)	min	typ	max	Unit
Wavelength		650		nm
Optical Output Power		16		mW
Operating Voltage	20	24	26	V DC
Operating Current	10	20	30	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 10,000 h
RoHS	yes

Optical Parameters

Beam Shape	Line
Laser Class	2
Divergence	H - 1.0 mrad
Fan Angle	90°
Line Thickness	<1mm@0.3m
Operating Distance	0.3m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Protection Lens	yes
Focus	fixed (300mm)

Electrical Parameters

Potential of Housing	isolated
Connector	CON_7000-08331-0000000

Mechanical Parameters

Size	Ø20x80 mm
Material	aluminium
Cable length	100 mm

Wire type	22AWG, black, 3,6mm
Output Aperture	5.5 mm
Weight	63 g
Protection Class	IP51

(*) Over the complete operating temperature range

Features



- Operating Voltage 24V DC
- Isolated housing
- Laser Class 1
- Small laser head
- Protection lens

Picture



Cable color

Ground		black	GND
Positive		white	20 - 26, typ 24 V DC

Safety Label



Valid Revision

| 19-NOV-2018