

Line laser, red, 650 nm, 90°, 16 mW

LH650-16-24(20x80)-PL-C1500
Order Number: 70109115

Main Parameters (*)	min	typ	max	Unit
Wavelength		650		nm
Optical Output Power		16		mW
Operating Voltage	21.6	24	26.4	V DC
Operating Current	5	12	20	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty 1 years

Technical Parameters

Lifetime > 10,000 h
RoHS yes

Optical Parameters

Beam Shape	Line
Laser Class	2
Divergence	H - 1.0 mrad
Fan Angle	90°
Line Thickness	<2mm@3m
Operating Distance	3 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	fixed (3000mm)

Electrical Parameters

Potential of Housing	isolated
Stripping of cable cover	50 mm

Mechanical Parameters

Size	Ø20x80 mm
Material	aluminium
Cable length	1,500 mm
Wire type	24AWG, black, 3mm

Output Aperture	5.5 mm
Housing Color	black
Weight	70g
Stripping of wire	5 mm

(*) Over the complete operating temperature range

Features





- Operating Voltage 24 V DC
- Isolated housing
- Uniform line thickness
- Fan angle 90°
- Compact size

Picture



Cable color

Ground		black	GND
Positive		red	21.6 - 26.4, typ 24 V DC

Safety Label



Valid Revision

14 | 14-NOV-2024