

Line laser, red, 650 nm, 90°, 16 mW

LH650-16-3(14x45)-C2500
Order Number: 70123029

Main Parameters (*)	min	typ	max	Unit
Wavelength		650		nm
Optical Output Power		16		mW
Operating Voltage	2.7	3	3.3	V DC
Operating Current	40	65	85	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty 1 years

Technical Parameters

Lifetime > 5,000 h
RoHS yes

Optical Parameters

Beam Shape	Line
Laser Class	2
Divergence	H - 1.0 mrad
Fan Angle	90°
Line Thickness	<1.5mm@3m
Operating Distance	5m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	fixed (3000mm)

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 3.3V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3.3W max.
Stripping of cable cover	50 mm

Mechanical Parameters

Size	Ø14x45 mm
Material	aluminium

Cable length	2,500 mm
Wire type	22AWG, black, 3,6mm
Output Aperture	5.5 mm
Housing Color	black
Weight	70 g
Stripping of wire	5 mm

(*) Over the complete operating temperature range

Features



- High power
- Uniform line thickness
- Operating Voltage 3V DC
- Laser Class 2
- Fan angle 90°

Picture



Cable color

Ground		black	GND
Positive		white	2.7 - 3.3, typ 3 V DC

Safety Label



Valid Revision

| 23-JUL-2020