

## Line laser, red, 650 nm, 90°, 30 mW

LH650-30-24(20x80)-F3000-M12  
Order Number: 70142211

Main Parameters (*)	min	typ	max	Unit
Wavelength		650		nm
Optical Output Power		30		mW
Operating Voltage	21.6	24	26.4	V DC
Operating Current	10	40	70	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

### Main Data

Warranty 1 years

### Technical Parameters

Lifetime > 10,000 h  
RoHS yes

### Optical Parameters

Beam Shape	Line
Laser Class	2M
Divergence	H - 1.0 mrad
Fan Angle	90°
Line Thickness	<1.5mm@3m
Operating Distance	3m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Protection Lens	yes
Focus	fixed (3000mm)

### Electrical Parameters

Potential of Housing	isolated
Connector	CON-M12

Power Supply  
Power Supply, Output: 24V DC,  
Input: 100-240V AC, 50-60Hz,  
Output Power: 24W max.  
SYS 1308-2424-W2E | 2,1 x 5,5  
x 11 center positive

### Mechanical Parameters

Size	Ø20x80 mm
Material	aluminium
Output Aperture	5.5 mm
Housing Color	black
Weight	63 g
Protection Class	IP 64


(\*) Over the complete operating temperature range

### Features



- Operating Voltage 24 V DC
- Isolated housing
- Laser Class 2M
- Small laser head
- Protection lens

### Picture



### Safety Label



### Valid Revision

| 20-MAY-2022