

Line laser, red, 660 nm, 110°, 10 mW

LH660-10-5(22x90)110-F1500
Order Number: 70140682

Main Parameters (*)	min	typ	max	Unit
Wavelength	650	660	660	nm
Optical Output Power	5	10	15	mW
Operating Voltage	3	5	5	V DC
Operating Current	50	75	100	mA
Operating Temperature	-10		50	°C
Storage Temperature	-40		85	°C

Main Data

Warranty 1 years

Technical Parameters

Lifetime > 10,000 h
RoHS yes

Optical Parameters

Beam Shape	Line
Laser Class	1M
Divergence	B - 0.3 mrad
Fan Angle	110°
Line Thickness	<1mm@1.5m
Operating Distance	10 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	fixed (1500mm)

Electrical Parameters

Potential of Housing	isolated
Connector	2.5 mm DC socket (+ pole inner)
Power Supply	Power Supply with stripped/tinned wires, Output: 5V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3W max.

Mechanical Parameters

Size Ø22x90 mm

Material	aluminium
Cable length	1,000 mm
Wire type	24AWG, black, 3mm
Output Aperture	6 mm
Housing Color	black
Weight	63 g
Protection Class	IP 54

(*) Over the complete operating temperature range

Features



- Operating Voltage 5V DC
- Laser Class 1M
- Low cost
- Fan angle 110°
- Compact size

Picture



Cable color

Ground		black	GND
Positive		red	3 - 5, typ 5 V DC

Safety Label



Valid Revision

| 17-MAR-2022