

Line laser, red, 650 nm, 60°, 4 mW

LI650-4-5(10x30)60DEG-F100
Order Number: 70116885

Main Parameters (*)	min	typ	max	Unit
Wavelength		650		nm
Optical Output Power		4		mW
Operating Voltage	4.5	5	5.5	V DC
Operating Current	20	32	55	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Line
Laser Class	1
Divergence	1 - 1.5 mrad
Fan Angle	60°
Line Thickness	<0.3mm@0.1m
Operating Distance	0.1 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	fixed (100mm)

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 5V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3W max.

Mechanical Parameters

Size	Ø10x30 mm
Material	aluminium
Cable length	100 mm

Wire type	26AWG, 0,14mm²
Output Aperture	3 mm
Housing Color	black
Weight	3.5g
Stripping of wire	5 mm

(*) Over the complete operating temperature range

Features



- Fixed focus
- Low power consumption
- For medical devices
- Uniform line thickness
- Image processing

Picture



Cable color

Ground		black	GND
Positive		red	4.5 - 5.5, typ 5 V DC

Safety Label



Valid Revision

13 | 30-MAR-2022