

Dot laser, green, 520 nm, 4 mW

MDD520-4-24-F(12x50)-C150-2CON
Order Number: 70138092

Main Parameters (*)	min	typ	max	Unit
Wavelength		520		nm
Optical Output Power	3	4	5	mW
Operating Voltage	21.6	24	26.4	V DC
Operating Current	5	20	50	mA
Operating Temperature	-10		60	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	>6,000 h
RoHS	yes

Optical Parameters

Beam Shape	Dot
Laser Class	3R
Divergence	D - 0.5 mrad
Size of Laserdot	adjustable
Operating Distance	100 m
Optics	glass lens AR coated
Laser technology	Single Mode Diode
Focus	adjustable
internal modulation frequency	1 kHz

Electrical Parameters

Potential of Housing	isolated
Connector	JST

Mechanical Parameters

Size	Ø12x50 mm
Material	aluminium
Cable length	150 mm
Wire type	28AWG, Typ 1571

Output Aperture	5 mm
Housing Color	black
Weight	13 g

(*) Over the complete operating temperature range

Features



- Isolated housing
- Laser Class 3R
- Compact size
- Anti-reflex coating

Picture



Cable color

Ground		black	GND
Positive		red	21.6 - 26.4, typ 24 V DC
Modulation		green	

Safety Label



Valid Revision

| 05-APR-2019