

Line laser, green, 532 nm, 90°, 1 mW

MLD532-1-5(20x80)
Order Number: 70100884

Main Parameters (*)	min	typ	max	Unit
Wavelength		532		nm
Optical Output Power		1		mW
Operating Voltage	4.5	5	5.5	V DC
Operating Current		125		mA
Operating Temperature	15		30	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Line
Laser Class	1
Divergence	D - 0.5 mrad
Fan Angle	90°
Line Thickness	<0.7mm@1m
Operating Distance	1 m
Optics	glass lens AR coated
Beam Mode	TEM00
Laser technology	YVO4+KTP
Stability	+/- 20% @ 15-30°C
Focus	fixed (1000mm)
Warm up time	< 15 min

Electrical Parameters

Potential of Housing	isolated
Max. Mod. Frequency	10 kHz

Mechanical Parameters

Size	Ø20x80 mm
Material	aluminium
Cable length	100 mm
Wire type	26AWG, 0,14mm²
Output Aperture	5 mm
Housing Color	black
Weight	55 g

(*) Over the complete operating temperature range

Features




Picture



Cable color

Ground		black	GND
Positive		red	4,5 - 5,5, typ 5 V DC
Modulation		yellow	10 kHz

Drawing



Safety Label



Valid Revision

4 | 22-JUL-2020