

Line laser, infrared, 980 nm, 90°, 120 mW

MLH980-120-5(22x60)
Order Number: 70106794

Main Parameters (*)	min	typ	max	Unit
Wavelength		980		nm
Optical Output Power		120		mW
Operating Voltage	4.5	5	5.5	V DC
Operating Current	200	400	600	mA
Operating Temperature	-20		50	°C
Storage Temperature	-40		80	°C

Main Data

Warranty	1 years
----------	---------

Technical Parameters

Lifetime	> 5,000 h
RoHS	yes

Optical Parameters

Beam Shape	Line
Laser Class	3R
Divergence	H - 1.0 mrad
Fan Angle	90°
Line Thickness	<1.5mm@3m
Operating Distance	3 m
Optics	glass lens AR coated
Laser technology	Multi Mode Diode
Focus	fixed (3000mm)

Electrical Parameters

Potential of Housing	isolated
Power Supply	Power Supply with stripped/tinned wires, Output: 5V DC, Input: 100-240V AC, 50-60Hz, Output Power: 3W max.

Mechanical Parameters

Size	Ø22x60 mm
Material	aluminium
Cable length	100 mm

Wire type	26AWG, 0,14mm ²
Output Aperture	5.5 mm
Housing Color	black
Weight	53 g

(*) Over the complete operating temperature range

Features






- Operating Voltage 5 V DC
- Laser Class 3R
- Uniform line thickness
- Fan angle 90°
- Image processing

Picture



Cable color

Ground		black	GND
Positive		red	4.5 - 5.5, typ 5 V DC
Modulation		yellow	

Safety Label



Valid Revision

5 | 26-MAR-2021