

## Bracket

MULTI-MOUNT-21(45x75)-MAGNETIC  
Order Number: 70144253

| Main Parameters (*)   | min | typ | max | Unit |
|-----------------------|-----|-----|-----|------|
| Operating Voltage     |     |     | 0   | V DC |
| Operating Temperature | -20 |     | 50  | °C   |
| Storage Temperature   | -50 |     | 70  | °C   |

### Mechanical Parameters

|               |           |
|---------------|-----------|
| Size          | Ø45x75 mm |
| Material      | aluminium |
| Housing Color | black     |
| Weight        | 141 g     |

### Mount Parameter

|                                      |                |
|--------------------------------------|----------------|
| Total Height (h1)                    | 75 mm          |
| Height to Laseraxis (h2)             | 60 mm          |
| Height of Base (h3)                  | 25 mm          |
| Mount Diameter (d1)                  | Ø 21 mm        |
| Diameter of Base (d2)                | Ø 45 mm        |
| Width of Mount (b)                   | 26 mm          |
| Height of Mount (g)                  | 50 mm          |
| Height of Mount Head (k)             | 50 mm          |
| Depth of Mount (t)                   | 15 mm          |
| Angle of Rotation Alpha ( $\alpha$ ) | 360°           |
| Angle of Rotation Beta ( $\beta$ )   | $\pm 90^\circ$ |


(\*) Over the complete operating temperature range

## Features



- Anodized aluminium
- Very robust
- For industrial applications
- Magnetic

## Picture



## Safety Label



## Valid Revision

| 15-NOV-2023